

产品型号		BSD-WX3350/3280/3200		BSD-WX2350/2280/2200		BSD-WX1350/1280	
控制方式		PID微电脑					
显示方式		LCD					
对流方式		强制对流					
温控范围 (°C)		RT+5~60		4~60			
温控分辨率 (°C)		±0.1					
温控波动度 (°C)		±0.5 (37°C时)					
温控均匀度 (°C)		±1 (37°C时)					
湿度控制范围		-				50%RH~90%RH 波动: ±5%	
回旋频率范围 (rpm)		30~300					
回旋频率精度 (rpm)		±1					
振幅 (mm)		Φ26					
定时范围		0~999min/h					
摇板数量 (块)		1					
电源		AC220V 50/60Hz					
功率 (W)	350	1400		1800		2800	
	280	1200		1600		2400	
	200	1100		1500		-	
内胆尺寸 (mm)	350	1035×675×470					
	280	1010×590×470					
	200	1010×590×310				-	
外形尺寸 (mm)	350	1380×800×1010					
	280	1350×700×1000					
	200	1260×730×850				-	
摇板尺寸 (mm)	350	970×605					
	280	950×530					
	200	950×530				-	
标准配置 (ml×支)	350	2000ml×8					
	280	2000ml×6					
	200	500ml×20				-	
满载配置 (ml×支)	350	50ml×103/100ml×103/250ml×63/500ml×41/750ml×32/1000ml×22/2000ml×15/3000ml×11/5000ml×7					
	280	50ml×71/100ml×71/250ml×45/500ml×37/750ml×29/1000ml×18/2000ml×15/3000ml×8/5000ml×7					
	200	50ml×71/100ml×71/250ml×45/500ml×37/750ml×29/1000ml×18				-	
外包装尺寸 (W)	350	1540x1000x1240		1540x1000x1240		1540x1000x1240	
	280	1510x910x1190		1510x910x1190		1510x910x1190	
	200	1400x900x1030		1400x900x1030		-	
毛重 (Kg)		350 / 302 / 247		358 / 302 / 256		362/328	
净重 (Kg)		270 / 242 / 219		278 / 242 / 228		282/ 266	

注:本摇床技术参数的测试条件为环境温度25°C。