



立式恒速电动搅拌器

VERTICAL CONSTANT SPEED ELECTRIC MIXER

HD2025W(250W)



▶ 技术参数 Technical parameters

电源: Power:	AC220V±10%
控制操作方式: Control mode of operation:	按键 Keystroke
电机功率: Motor power:	250W
电机转矩: Motor torque:	1.2N·M
转速控制: Speed control:	无极 Infinity
速度显示: Speed display:	液晶 Liquid crystal
转速: Speed of revolution:	20-1300r/min
适用介质粘度: Applicable medium viscosity:	>100000mpas
搅拌容量(水): Maximum stirring capacity:	200-50000ml
定时时间: Timing Time:	0-9999min
转夹头夹持范围最小直径: Minimum diameter of clamping range of rotary chuck:	0.5mm
转夹头夹持范围最大直径: Maximum diameter of clamping range of rotary chuck:	13mm
延长臂直径: Extension arm diameter:	16mm
延长臂长度: Extension arm length:	200mm
重量: Weight:	18.5KG
外形尺寸: Dimension:	450x350x770mm
允许环境温度: Allowable ambient temperature:	0-40°C
允许相对湿度: Allowable relative humidity:	80%
标配搅拌桨: Standard mixing paste:	一字型不锈钢搅拌桨 A type of stainless steel mixing slurry.

优点 恒速电动搅拌器采用深度闭环,所以在低速时能在恒功率工作,调速采用轻触开关,可逆转搅拌。

Advantages: constant speed electric mixer adopts deep closed loop, so at low speed it can work at constant power. The speed adjustment adopts the light touch switch, which can reverse stirring.

备注: 转速显示: 液晶屏上行测得转速,下行转向和设定转速。

Note: Speed display: the LCD can measure the speed on the upward side, and turn and set the speed on the downward side.

立式恒速电动搅拌器

VERTICAL CONSTANT SPEED ELECTRIC MIXER



HD2010W(100W)



HD2015W(150W)

▶ 技术参数

Technical parameters	HD2015W(150W)	HD2010W(100W)	HD2004W(40W)
电源: Power:	AC220V±10%	AC220V±10%	AC220V±10%
控制操作方式: Control mode of operation:	按键 Keystroke	按键 Keystroke	按键 Keystroke
电机功率: Motor power:	150W	100W	40W
电机转矩: Motor torque:	0.8N·M	0.6N·M	0.3N·M
转速控制: Speed control:	无极 Infinity	无极 Infinity	无极 Infinity
速度显示: Speed display:	液晶 Liquid crystal	液晶 Liquid crystal	液晶 Liquid crystal
转速: Speed of revolution:	20-1300r/min	20-1300r/min	20-1600r/min
适用介质粘度: Applicable medium viscosity:	100000mpas	50000mpas	10000mpas
搅拌容量(水): Maximum stirring capacity:	200-30000ml	200-20000ml	200-10000ml
定时时间: Timing Time:	0-9999min	0-9999min	0-9999min
转夹头夹持范围最小直径: Minimum diameter of clamping range of rotary chuck:	0.5mm	0.5mm	0.5mm
转夹头夹持范围最大直径: Maximum diameter of clamping range of rotary chuck:	13mm	13mm	10mm
延长臂直径: Extension arm diameter:	16mm	16mm	16mm
延长臂长度: Extension arm length:	200mm	200mm	200mm
重量: Weight:	12KG	12KG	11.5KG
外形尺寸: Dimension:	350x250x770mm	350x250x770mm	350x250x770mm
允许环境温度: Allowable ambient temperature:	0-40°C	0-40°C	0-40°C
允许相对湿度: Allowable relative humidity:	80%	80%	80%
标配搅拌桨: Standard mixing paste:	十字型不锈钢搅拌桨 Cross type	十字型不锈钢搅拌桨 Cross type	四氟搅拌桨 tetrafluoroethyl stirring paddle

优点: 恒速电动搅拌器采用深度闭环,所以在低速时能在恒功率工作;调速采用轻触开关,可逆转搅拌。

Advantages: constant speed electric mixer adopts deep closed loop, so at low speed it can work at constant power. The speed adjustment adopts the light touch switch, which can reverse stirring.

备注: 转速显示: 液晶屏上行测得转速,下行转向和设定转速。

Note: Speed display: the LCD can measure the speed on the upward side, and turn and set the speed on the downward side.